

PPC



**SP-6128 /
SP-6120 /
SP-6122**

**Fanless and Low Power
8.4" / 10.4" / 12.1" Intel®
N2800/D2550 processor
Panel PC**

Features and Benefits:

- Intel® N2800/D2550 processor on board
- Supports Intel® NM10
- Totally fanless and quiet design
- Support CFast slot
- Optional Wireless LAN module
- Support wide voltage DC in (9~36V)
- Aluminum front bezel



Protech Systems Co., Ltd.

No. 24, Lane 365, Yang Goang Street, Nei Hu District Taipei 114, Taiwan
TEL: +886-2-8751-1111 FAX: +886-2-8751-1199
E-mail: sales@protech.com.tw
<http://www.protech.com.tw>

Distributed by :



KeyProLine Eurl
Le Causse De Dumié - 82300 Saint Cirq
Tel : (+33) 09-62-55-62-88 - Fax : (+33) 05-63-03-54-41
Site internet : www.keyproline.com
@mail : keyproline@keyproline.com



ISO CERTIFIED

9001 14001

SP-6128 / SP-6120 / SP-6122

Fanless and Low Power 8.4" / 10.4" / 12.1" Intel N2800/D2550 processor Panel PC

Front View

Rear View

Side View

SP-6128 / SP-6120 / SP-6122

SP-6128


SP-6120

SP-6122

SP-6128

SP-6120

SP-6122



Unit: mm

Specification

Systems	
CPU Type	Intel® N2800/D2550 processor
Chipset	Intel® NM10
Memory Support	1 x DDR III SO-DIMM socket (memory up to 4GB)
Front Bezel	Aluminum
IP65	Yes (for front panel only)
Power requirement	DC in 9~36V
O.S. Support	Windows7
Dimension	SP-6128: 246.8 mm x 184.6mm x 71mm (9.71" x 7.27" x 2.8") SP-6120: 277.6mm x 228.8 mm x 72mm (11" x 9" x 2.83") SP-6122: 324mm x 246 mm x 72mm (12.76" x 9.69" x 2.83")
System Weight	SP-6118: 2.9Kg SP-6110: 3.5Kg SP-6112: 4.1Kg
VESA Mounting Support	VESA 75
Certificate	FCC / CE

I/O Ports

USB	2 x USB 2.0
Audio	1 x Line-out, 1 x Mic-in
Serial Port	2 x COM port (support +5V/ +12V/RI selectable), COM 2 for RS232/422/485 selectable
LAN	2 x LAN (10/100/1000 Mbps)
DVI	1 x DVI-I
Drive Bay	1 x 2.5" SATA HDD
Expansion Slots	1 x CFast slot, 1 x mini PCIe slot

Display

LCD	SP-6128: AUO 8.4" LED backlight LCD, resolution 800 x 600 SP-6120: 10.4" SVGA or XGA LCD Panel SP-6122: AUO 12.1" LED backlight LCD, resolution 1024 x 768
Touch Screen	(ELO) 5W Analog resistive (USB interface)

Environment

Operation Temp.	0° ~ 45° C (32° ~ 113° F) (w/HDD) 0° ~ 55° C (32° ~ 131° F) (w/Wide temperature CFast card) (w/o Audio)
Storage Temp.	- 20° ~ 60 ° C (- 4° ~ 140° F)
Humidity	20% ~ 90%

Ordering Information

SP-6128RA-A0B	8.4" fanless Intel® N2800 Panel PC, w/AUO 8.4" 800 x 600 LCD / 5-Wire ELO touch
SP-6128RA-B0B	8.4" fanless Intel® D2550 Panel PC, w/AUO 8.4" 800 x 600 LCD / 5-Wire ELO touch
SP-6120RA-A0B	10.4" fanless Intel® N2800 Panel PC, w/AUO 10.4" 800 x 600 LCD / 5-Wire ELO touch
SP-6120RA-B0B	10.4" fanless Intel® D2550 Panel PC, w/AUO 10.4" 800 x 600 LCD / 5-Wire ELO touch
SP-6120RA-C0B	10.4" fanless Intel® N2800 Panel PC, w/CPT 10.4" 1024 x 768 LCD / 5-Wire ELO touch
SP-6120RA-D0B	10.4" fanless Intel® D2550 Panel PC, w/CPT 10.4" 1024 x 768 LCD / 5-Wire ELO touch
SP-6122RA-A0B	12.1" fanless Intel® N2800 Panel PC, w/AUO 12.1" 1024 x 768 LCD / 5-Wire ELO touch
SP-6122RA-B0B	12.1" fanless Intel® D2550 Panel PC, w/AUO 12.1" 1024 x 768 LCD / 5-Wire ELO touch
52-002-11072302	72W, 24Vdc output power adaptor

All of trademarks and brand names are the property of their owners. Trademark "Protech" is the property of Protech Systems Co., Ltd. All information contained in this document is subject to change without any prior notice. This catalog is copyrighted in Dec. 2012.